

FORM PTO-1390 (Modified)
(REV 11-98)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371

RCA 89383

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR

09/913097

INTERNATIONAL APPLICATION NO.

PCT/US00/02989

INTERNATIONAL FILING DATE

04 FEBRUARY 2000 (04.02.00)

PRIORITY DATE CLAIMED

09 FEBRUARY 1999 (09.02.99)

TITLE OF INVENTION

CONTROL OF SCANNING VELOCITY MODULATION AT MULTIPLE SCANNING FREQUENCIES

APPLICANT(S) FOR DO/EO/US

Jeffrey Owen Allender and Gene Karl Sendelweck

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371 (c) (2))
 - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ A copy of the International Search Report (PCT/ISA/210). attached to Item 13
8. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
9. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
10. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).
11. ☒ A copy of the International Preliminary Examination Report (PCT/IPEA/409).
12. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).

Items 13 to 20 below concern document(s) or information included:

13. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98. with references attached.
14. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
15. ☒ A **FIRST** preliminary amendment.
16. ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
17. ☐ A substitute specification.
18. ☐ A change of power of attorney and/or address letter.
19. ☒ Certificate of Mailing by Express Mail
20. Return postcard receipt

20. XXXXX Other items or information

CERTIFICATE OF MAILING UNDER 37 CFR 1.10

EL682442750US

AUGUST 9, 2001

"Express Mail" mailing no.

Date of Deposit

I hereby certify that this application is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Anelia Urban

Anelia Urban

Typed or printed name of person
mailing applicationSignature of person mailing
application

CALCULATIONS PTO USE ONLY

(5):

- International preliminary examination fee (37 CFR 1.482) nor
International Search Report prepared by the EPO or JPO\$1000.00
- ☐ International preliminary examination fee (37 CFR 1.482) not paid to
USPTO but International Search Report prepared by the EPO or JPO\$860.00
- ☐ International preliminary examination fee (37 CFR 1.482) not paid to USPTO
but international search fee (37 CFR 1.445(a)(2)) paid to USPTO\$710.00
- ☐ International preliminary examination fee paid to USPTO (37 CFR 1.482)
but all claims did not satisfy provisions of PCT Article 33(1)-(4)\$690.00
- ☐ International preliminary examination fee paid to USPTO (37 CFR 1.482)
and all claims satisfied provisions of PCT Article 33(1)-(4)\$100.00

ENTER APPROPRIATE BASIC FEE AMOUNT =

860.00

Surcharge of \$130.00 for furnishing the oath or declaration later than ☐ 20 ☐ 30
months from the earliest claimed priority date (37 CFR 1.492 (e)).

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE
Total claims	14 - 20 =	0	x \$18.00
Independent claims	3 - 3 =	0	x \$80.00

Multiple Dependent Claims (check if applicable). ☐

TOTAL OF ABOVE CALCULATIONS =

Reduction of 1/2 for filing by small entity, if applicable. Verified Small Entity Statement
must also be filed (Note 37 CFR 1.9, 1.27, 1.28) (check if applicable). ☐

SUBTOTAL =

860.00

Processing fee of \$130.00 for furnishing the English translation later than ☐ 20 ☐ 30
months from the earliest claimed priority date (37 CFR 1.492 (f)). +

TOTAL NATIONAL FEE =

860.00

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be
accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable). ☐

TOTAL FEES ENCLOSED =

Amount to be:

refunded

\$

charged

\$ 860.00

- ☐ A check in the amount of _____ to cover the above fees is enclosed.
- ☒ Please charge my Deposit Account No. 07-0832 in the amount of \$860.00 to cover the above fees.
A duplicate copy of this sheet is enclosed.
- ☒ The Commissioner is hereby authorized to charge any fees which may be required, or credit any overpayment
to Deposit Account No. 07-0832 A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR
1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

Mr. Joseph S. Tripoli
THOMSON multimedia Licensing Inc.
Patent Department
PO Box 5312
Princeton, New Jersey 08540

SIGNATURE

Francis A. Davenport

NAME

36,136

REGISTRATION NUMBER

August 9, 2001

DATE

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : Jeffrey Owen Allender and Gene Karl Sendelweck
Filed : February 4, 2000 - PCT National Phase of PCT/US00/02989
For : CONTROL OF SCANNING VELOCITY MODULATION AT
MULTIPLE SCANNING FREQUENCIES

PRELIMINARY AMENDMENT

Hon. Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Sir:

In the US national phase application of PCT/US00/02989
please enter the following amendments.

IN THE SPECIFICATION (As Annexed to the International Preliminary
Examination Report:

Please amend the specification as follows:

Page 1, line 3, after the title, insert the following:

--This application claims the benefit under 35 U.S.C.

§ 365 of International Application PCT/US00/02989 filed February 4, 2000,
which claims the benefit of U.S. Provisional Application No. 60/119,278,
filed February 9, 1999.--

IN THE CLAIMS (As Annexed to the International Preliminary Examination
Report:


Page 12, line 1 delete title, "Claims" and replace with --What is
claimed is:--

REMARKS

The specification has been amended to include a reference to the priority applications.

No fee is believed to have been incurred by virtue of this amendment. However if a fee is incurred on the basis of this amendment, please charge such fee against deposit account 07-0832.

Respectfully submitted,
Jeffrey Owen Allender
Gene Karl Sendelweck


Francis A. Davenport
Registration No. 36,316
609/734-9864

THOMSON multimedia Licensing Inc.
Patent Operation
PO Box 5312
Princeton, NJ 08543-5312

August 9, 2001

ART 34 AMDT

1

CONTROL OF SCANNING VELOCITY MODULATION AT
MULTIPLE SCANNING FREQUENCIES

This invention relates to scanning velocity modulation (SVM) systems and more particularly to the automatic control of scanning velocity modulation signal amplitude at multiple scanning frequencies.

BACKGROUND OF THE INVENTION

It is well known that in a cathode ray tube display an improvement in apparent picture sharpness can be achieved by modulating the scanning velocity of an electron beam in accordance with the derivative of the luminance portion of the display signal. This derivative signal, or scan velocity modulation signal, can be derived from the luminance portion of the video signal and identifies when scanning beam velocity variations should be employed. Slowing of the scanning velocity of the electron beam causes a greater number of electrons to land at a particular point in the display resulting in brightening of the video monitor display at that particular location on the display. Conversely, accelerating the scanning velocity at a particular portion of the screen results in display darkening. Thus, horizontal rate edges may be visually enhanced by variations in the display intensity at edge transitions caused by the variation of the electron beam speed. This method of picture sharpness enhancement has advantages over a peaking approach to picture sharpness enhancement such as an avoidance of blooming of peaked high luminance (white) picture elements and an avoidance of enhancement of video noise occurring within the bandwidth of the peaked signals.

In Japanese Patent 61-099467 and PAJ vol. 010, No. 279 a multiscan TV receiver is disclosed which employs scanning beam velocity modulation by modulating the voltage applied to a fourth grid of the CRT. The reference also teaches that the velocity modulating voltage applied to the CRT grid is also applied to a peak to peak detector (83). The output from detector (83) is coupled to an AGC circuit (82) which controls the amplitude of the velocity modulating voltage applied to the CRT. In this way a closed loop is formed which maintains the peak to peak value of the velocity modulating voltage at a prescribed amount. Separated horizontal syncs are fed to

1/1

1 discriminator (84) which produces an output signal that is applied to control a
2 time constant of AGC circuit (82).

3 A TV receiver which employs scanning beam velocity modulation by
4 means of a magnetic deflection coil is disclosed in US Patent 5982449 and EPO
5 784 402 A2. A signal for SVM signal derivation is coupled via a digital filtering
6 means (12) which is programmed by CPU (3) based on information derived from
7 the format or content of the input signal selected for display. In this way the
8 sharpness of the displayed image is adapted to the input signal selected. This
9 reference also discloses the use of an SVM driver current feedback loop where
10 driver current is converted to a digital signal and coupled to CPU (3) to change
11 the characteristic of the programmable filter means (12).

12 SVM systems, such as those described above, are well known for
13 use in television systems, but they are typically not used in computer monitors.
14 SVM systems are generally not well suited for use in monitors that display video
15 signals of various different formats such as VGA, or SVGA which may use
16 alternative scanning frequencies. The horizontal scanning rates of these video
17 formats can be anywhere from 2 to 2.4 times as great as an NTSC horizontal
18 scanning frequency. With the convergence of the television and the computer
19 monitor, SVM is starting to be used under much more demanding conditions.
20 For example, multimedia monitors are becoming available that are also capable of

handling computer formats. This presents significant problems as concerns use of SVM. Not only are computer monitor horizontal scan rates greater than conventional NTSC scan rates, but new high definition television scan rates defined by the Advanced Television System Committee (ATSC) standards can also be as much as 2.14 times greater than NTSC television scan rates. Thus, for example, if the NTSC television systems are referred to as having a scan frequency of 1H, then VGA, HDTV and SVGA systems can be said to have scan frequencies of 2H, 2.14H and 2.4H, respectively.

One problem with the use of SVM technology in connection with displays that are to be used for video signals at a variety of different scan rates is that there is generally a doubling in SVM signal amplitude for every octave increase in horizontal scanning frequency. For example, the SVM signal generated from the derivative of a luminance component of a 2H scanning frequency signal will generally be 6 dB greater than the SVM signal which is generated for an NTSC (1H) signal. This amplitude range can result in an SVM signal that is less than optimal. In particular, when SVM systems are used in fixed scanning rate displays, the application of scan velocity modulation to any video signal is optimized having a predetermined range of amplitudes for signal processing at the particular scan rate at which the display is to be used. However, when a display is operable at multiple scan rates, it is much more difficult to optimize SVM signal processing since the range of SVM amplitudes can at least double for the various video signal formats. For example, if scan velocity modulation in a multiple scan rate monitor is optimized for 1H video signals, then excess SVM signal amplitude can result causing blooming or other undesirable artifacts when required to function with a 2H video signal. Similarly, when scan velocity modulation in a multiple scan rate monitor is optimized for 2H video signals, the SVM signal amplitude will be too small to provide sufficient image enhancement for 1H signal inputs. It is thus desirable to determine a way in which to ensure that a predetermined range of SVM signal amplitudes is used, regardless of the scan frequency rate of a particular video display format.

SUMMARY OF THE INVENTION

In an inventive method scanning velocity modulation signal amplitude is controlled at a plurality of horizontal scanning frequencies. The method comprises the steps of, generating respective scanning velocity modulation signals from signals having a plurality of horizontal scanning frequencies and coupled for display by said apparatus, and, selectively controlling an amplitude of each respective scanning velocity modulation signal to a predetermined range of amplitudes.

According to one aspect of the invention, the amount of gain applied to the scan velocity modulation signal is reduced as the frequency of the horizontal scanning frequency is increased. For example, gain can be reduced by 6dB for each octave increase in horizontal scanning frequency so as to compensate for the differences introduced by the horizontal scanning frequency associated with various video formats.

According to another aspect of the invention, the horizontal scanning frequency is determined by a scan frequency detector circuit. In this case, the control signal is a DC voltage generated by said scan frequency detector which varies proportionally as a function of the horizontal scanning frequency. This DC voltage can then be used to directly control an amplifier gain. Alternatively, the control signal can be a digital command signal generated by a microprocessor responsive to horizontal scan frequency selection data. In that case, the digital command signal is preferably used to selectively vary an SVM gain register for controlling the amplitude of the SVM signal.

In an alternative embodiment the SVM amplitude control signal can be a digital command signal generated by a microprocessor responsive display source selection data. In that case, the digital command signal is preferably used to selectively vary an SVM gain register for controlling the SVM signal amplitude.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGURE 1 is a graph of SVM signal amplitude versus scanning frequency.

FIGURE 2 is a block diagram of an inventive SVM automatic gain control system for controlling an SVM signal amplitude.

FIGURE 3 is a detailed circuit diagram showing an embodiment of an SVM circuit with an automatic gain control system according to FIGURE 2.

FIGURE 4 is a block diagram of an alternative inventive embodiment employing an SVM automatic gain control system according to FIGURE 2..

FIGURE 5(a) shows an SVM signal output from a differentiator for a 1H video signal.

FIGURE 5(b) shows the signal of FIGURE 5(a) after amplitude control.

FIGURE 5(c) shows an SVM signal output from a differentiator for a 2H video signal.

FIGURE 5(d) shows the signal of FIGURE 5(c) after amplitude control.

DETAILED DESCRIPTION

Figure 1 is a plot showing SVM signal amplitude versus scan frequency in a display operable at multiple scanning frequencies. The y-axis represents the SVM signal amplitude, for example in decibels, when generated by a conventional SVM differentiator circuit. The x-axis represents horizontal scanning frequency of an input video signal. The standard NTSC horizontal frequency is denoted by 1H, hence, 2H denotes a scanning frequency which is one octave higher, for example, as used for 640x480 video format. FIGURE 1 illustrates that the SVM signal amplitude increases by about 6dB for video signals having horizontal scanning frequencies in the 2H or greater frequency band. Thus, an SVM circuit designed for specific performance parameters, such as peak to peak clipping and noise coring with in a predetermined range of SVM signal amplitudes with 1H signals, can be over driven when processing SVM signals derived from video signals in the 2H frequency band. Overdriving an SVM system can for example result in, SVM output drive signal clipping, the output driver amplifier operating in a power limitation condition, with in addition, continuous peak to peak clipper activation and attendant loss of image sharpness enhancement. Alternatively, if the SVM circuitry is designed for optimal performance with a range of SVM signal amplitudes derived from 2H video signals, but receives a 1H signal, the SVM signal amplitude will be too small, possibly even failing to overcome the signal range for noise coring, and certainly resulting in insufficient picture enhancement.

FIGURE 2 depicts in block diagram form an open loop SVM automatic gain control system for adjusting SVM signal amplitude to be within a predetermined amplitude range when operating with video formats having different spatial resolution and different scanning frequencies. In FIGURE 2, a video signal which includes horizontal frequency information is applied to derivative circuit 1. In derivative circuit 1, the luminance component of the video signal is differentiated to produce an SVM signal. The output of derivative circuit 1 is coupled to variable gain amplifier 2. There, the SVM signal is amplified and is used to generate a deflection current in the SVM coil for modulating the beam scanning velocity.

According to a preferred embodiment of the invention, scanning frequency detector 3 makes use of a portion of the input signal containing horizontal scanning frequency information to provide an indicator of likely spatial frequency content of the input signal. In simple terms, FIGURE 1 shows the increase in SVM signal amplitude that occurs with a doubling of input frequency. Since an exemplary ATSC image is capable of at least double the horizontal resolution of an NTSC signal, an open loop feed forward SVM amplitude control signal based on horizontal sync frequency determination provides a reliable indication of the spectral content of the displayed image.

To control the gain or SVM signal amplitude generated by amplifier 2 the horizontal scanning frequency is monitored and when it increases above 1H, the feed forward control signal from scan frequency detector 3 causes the SVM signal from amplifier 2 to be reduced in amplitude. Furthermore, open loop SVM signal gain and or amplitude control can be applied generally in accordance with a complementary or inverse transfer function to that depicted in FIGURE 1. Thus, gain, or SVM amplitude, is preferably halved for signals having double frequency scanning rates. Conversely, SVM amplitude or gain can similarly be increased for a corresponding decrease in horizontal scanning frequency.

FIGURE 3 is a detailed circuit diagram showing an embodiment of the SVM automatic gain control system of FIGURE 2. As shown in FIGURE 3, a luminance signal with negative going horizontal sync is applied to the input of the circuit. This signal can be provided by horizontal sync, luminance (Y) with

1 sync. The input video signal passes through AC coupling capacitor C1 which is
2 coupled to the base electrode of transistor Q2, an emitter follower. Resistors
3 R10, R11 and R12 form a potential divider and set the base voltages of
4 transistors Q2 and Q4. The collector electrode of transistor Q2 is coupled to a
5 source of operating potential, +VA, typically 24 volts, and its emitter is coupled
6 through resistor R13 to the emitter electrode of grounded base amplifier Q4.
7 The base electrode of transistor Q4 is biased from the junction of resistors R11
8 and R12 and is decoupled ground via capacitor C2.

9 The input video signal is differentiated in the collector circuit of
10 transistor Q4 by the parallel configured network comprising capacitor C5,
11 inductor L2 and damping resistor R19 thus producing an SVM signal. The output
12 of the differentiator circuit is coupled via series connected capacitor C3 and
13 resistor R20 to the base of transistor Q6. A resistor R21 is coupled to the
14 junction of capacitor C3 and resistor R20 to bias the base of transistor Q6 to the
15 same potential as that of transistor Q8. Transistors Q6 and Q8 form a
16 differential amplifier in which the gain is set by resistors R26 and R28, R36 and
17 the collector current of current source transistor Q7. Resistors R25, R33 and
18 R34 form a potential divider that provides biasing voltages for transistors Q6,
19 Q7, and Q8, where transistor Q6 is biased via resistors R20 and R21 and
20 transistor Q8 is biased via resistor R30. The junction of resistors R21, R30, R33
21 and R34 is decoupled to ground by capacitor C14. Similarly capacitor C11
22 decouples the junction of resistors R25 and R33 to ground. The collector
23 electrode of Q6 is coupled to supply voltage +VA, and the collector electrode of
24 transistor Q8 is coupled to supply voltage +VA through collector load resistor
25 R36. Additionally, the SVM signal output of the differential amplifier is taken
26 from the collector electrode of transistor Q8.

27 Moving to the scan frequency detector portion of the circuit, the
28 video signal with negative going horizontal frequency information is applied via
29 capacitor C6 to the base electrode of PNP transistor Q3 which is biased by
30 resistor R14 which is connected to ground. Transistor Q3 is configured as a
31 negative going pulse detector which outputs at its collector, a positive going
32 horizontal rate pulse signal derived from the horizontal sync frequency of the

1 incoming video signal. The emitter of transistor Q3 is coupled to operating
2 potential +VA. Series connected resistors R16 and R17 form a collector load
3 for transistor Q3. The positive pulses from the collector are coupled via resistor
4 R17, which determines a charging current for capacitor C8. During intervening
5 pulse periods capacitor C8 is discharged to ground via resistor R16 thus forming
6 a horizontal rate sawtooth signal. The sawtooth waveform is then applied to the
7 base electrode of transistor Q5, an emitter follower, that buffers the sawtooth
8 signal. The collector electrode of transistor Q5 is coupled to supply voltage
9 +VA, and the emitter electrode is coupled through resistor R15 to ground. The
10 emitter of transistor Q5, is also coupled to resistor R18 and capacitor C7 which
11 form a low pass filter that converts the sawtooth signal into a DC voltage having
12 a value in proportion to the horizontal sync frequency of the input video signal,
13 i.e. the higher the horizontal frequency the greater the resultant DC voltage.
14 This frequency dependent DC voltage is coupled to the base of emitter follower
15 transistor Q10 which provides a current I via resistor R19 to the junction of
16 resistor R27 and the emitter of the differential amplifier current source transistor
17 Q7. The collector electrode of transistor Q7 is coupled to the junction of
18 resistors R26 and R28, and the emitter electrode is coupled to ground via
19 resistor R27. As the DC voltage from the scanning frequency detector
20 increases, the voltage at the emitter of transistor Q7 increases causing the base
21 emitter potential to be reduced which in turn reduces the collector current. Thus
22 the current supply to the differential amplifier is reduced causing the SVM output
23 signal at transistor Q8 collector to be reduced in amplitude. The reduction in
24 source current of the differential amplifier causes a decrease in the gain of the
25 SVM signal. Thus, the differential amplifier comprised of the transistors Q6, Q7
26 and Q8 is configured as a variable gain amplifier in which the output signal
27 amplitude is automatically reduced when horizontal scanning frequency of the
28 display signal is increased.

29 It may be readily appreciated that the embodiment of the invention
30 in FIGURE 2 is not limited to the precise arrangement shown and that there are
31 other alternatives for implementing the control system according to the present
32 invention. In fact, the present invention can be implemented using any circuit

1 that detects a horizontal scan frequency of a video signal and then modifies SVM
2 signal amplitude to maintain optimal SVM performance at different scan
3 frequencies. FIGURE 4 depicts one such alternative embodiment.

4 In FIGURE 4, input stage 10 is shown with a plurality of user
5 selectable video input sources including several 1H video sources such as NTSC
6 composite video (VID 1, 2, 3, 4), S-video (SVID 1, 2, 3) and component video (Y
7 Pr Pb). In addition, input stage 10 typically has one or more input connections
8 providing user selectable 2H and higher scanning frequency video sources
9 including VGA 1, VGA 2 and HDTV. It should be noted that the invention is not
10 limited in this regard. Other video sources may also be provided and not all of
11 the video sources identified need be supplied.

12 In a further embodiment shown in FIGURE 4, when the user
13 selected input is an NTSC or other 1H input, the horizontal (H) sync pulses and
14 vertical (V) sync pulses are extracted by a video processor, depicted by
15 exemplary integrated circuit 11, from the composite video or luminance signal
16 components of the selected 1H source. Video processor 11 then outputs the H
17 and V sync pulses separated from the 1H sources to H & V selector switch 12
18 for selection and coupling to microprocessor 13. The processing features of
19 video processor 11 can be provided by an integrated circuit, for example type
20 TA1276N which is commercially available from Toshiba. However, the invention
21 is not limited in this regard and those skilled in the art will recognize that discrete
22 component circuitry or any other commercially available integrated circuit having
23 similar capabilities can also be used for this purpose.

24 An up-converter 16 can be provided between input stage 10 and
25 video processor 11. Up-converter 16 is used to convert NTSC or other 1H video
26 signals to 2H video signals and can, for example, be implemented by line
27 doubling. As shown in FIGURE 4, up-converter 16 is controlled by
28 microprocessor 13 via a data bus, for example, employing an I²C protocol, based
29 on a determination of the selected input horizontal frequency by microprocessor
30 13.

31 Referring again to block 10 of FIGURE 4, the 2H or higher input
32 signals may provide separate horizontal and vertical sync pulses, which when

1 selected, via the data bus, are directly coupled to H & V selector switch 12 and
2 ultimately to microprocessor 13 for further processing. In the case of these 2H -
3 2.4H video sources, video processor 11 will preferably receive the component
4 video signals (R, G, B) as shown, with selection within processor 11 controlled
5 by microprocessor 13 via the I²C bus.

6 As has been described, microprocessor 13 is variously coupled to
7 provide control via the I²C bus. Microprocessor 13, can for example be an ST
8 9296 IC which is commercially available from ST Microelectronics. However,
9 the invention is not limited in this regard and any other microprocessor of similar
10 capability can be used for this purpose.

11 As depicted in FIGURE 4, microprocessor 13 receives selected H
12 and V sync pulses from H & V selector switch 12 to determine the horizontal
13 frequency of the video source selected for display and SVM enhancement.
14 Microprocessor 13 can determine the horizontal frequency of the selected display
15 signal by a number of methods. For example, as described with reference to
16 FIGURE 2, a frequency dependent voltage may be generated, with the resulting
17 DC value measured by microprocessor 13 and compared with stored values to
18 determine the horizontal frequency of the selected source. In a second method
19 microprocessor 13 can measure a duration or width of an element of the
20 selected horizontal sync pulse to determine the horizontal scanning frequency.
21 In a further method, since microprocessor 13 is responsive to user selection of
22 display signal input, horizontal frequency indicating logic can, for example, be
23 implemented by hard wiring or a look up table to associate the user selected
24 input signal with a specific input signal format and scanning frequency.
25 Furthermore, since various display signals are connected to the display device via
26 mechanically different connectors, the horizontal frequency determination can be
27 derived from the input socket selected. For example NTSC signals, S-video
28 signals and SVGA signals are each input to the display via differing, non-
29 interchangeable connectors. Thus, based on one or a combination of the various
30 horizontal frequency determination methods, microprocessor 13 is preferably
31 programmed to send a horizontal frequency specific gain or amplitude control
32 command via the data bus to video processor 11. Video processor 11

1 preferably contains an SVM generator with gain or SVM output signal amplitude
2 controlled in response to control command data received from microprocessor 13
3 via the I²C bus. For example, in the case of IC type TA 1276N previously noted,
4 the SVM gain is controlled by a 2-bit register that can attenuate the SVM signal
5 by 0dB, -6dB, -9dB, with in addition, the capability of inhibiting the SVM signal
6 output. Microprocessor 13 is preferably programmed such that the SVM signal
7 is not attenuated, ie gain is set to 0dB when 1H video sources are determined,
8 and for 2H sources microprocessor 13 generates control data which provides a -
9 6dB reduction in of SVM signal gain. Video sources with scan rates higher than
10 2H are preferably attenuated in accordance with the transfer function illustrated
11 in FIGURE 1. In general, for each octave increase in scanning frequency, the
12 SVM signal is attenuated 6dB to maintain the SVM signal within a predetermined
13 range of amplitudes. As shown in FIGURE 4, the controlled amplitude SVM
14 signal is coupled to SVM driver 14 and ultimately SVM coil 15 to produce
15 substantially similar image enhancement, independent of the display scanning
16 frequency.

17 As described previously, NTSC or other 1H video signals can be
18 converted into 2H video signals by up-converter 16. In this way signals with
19 inherently lower image detail, or spatial resolution, are converted and receive
20 detectable attributes indicative of 2H video signals. However, although such up
21 converted signals may be detected as 2H video signals, the image detail is not
22 comparable with that of a signal that originated as 2H signal. In simple terms
23 the up conversion process cannot add image detail absent from the original 1H
24 image. Thus it can be appreciated that although these signals may be detected
25 as 2H video signals, the displayed image can benefit from a level of SVM
26 enhancement greater than that provided for original 2H signals. Thus when up-
27 converter 16 is enabled, microprocessor 13 can determine from an exemplary
28 look up table or the like, an amplitude control value suitable for SVM
29 enhancement of such up-converted images. For example, an up converted image
30 can receive an SVM amplitude value between those provided for 1H and 2H
31 frequency sources.

FIGURES 5(a), 5(b), 5(c) and 5(d) illustrate the problem identified by applicants and the advantageous amplitude control solution described herein. FIGURE 5(a) shows an example of an SVM signal at an output of a differentiator or SVM signal generator. The SVM signal was formed by differentiation of a 1H luminance signal component comprising a 100 IRE pulse with 60 nanosecond rise and fall times. FIGURE 5(c) shows an SVM signal formed by differentiation of a 2H video signal comprising a 100 IRE pulse with 30 nanosecond rise and fall times. The exemplary waveforms for FIGURES 5(a) and 5(c) are chosen to be visually equal, when displayed. Both of these signals are depicted with reference to the output of derivative circuit 1 of FIGURE 2. As described earlier, the SVM signal resulting from the 2H source is depicted with approximately twice the amplitude of the SVM signal derived from the 1H source.

Referring now to FIGURES 5(b) and 5(d), the effects of the advantageous automatic control system are shown according to a preferred embodiment of the invention. FIGURE 5(b) illustrates the amplitude of the 1H SVM output signal as measured from the output of variable gain amplifier 2 in FIGURE 2. FIGURE 5(d) shows the amplitude of the 2H SVM output signal similarly measured at the output of variable gain amplifier 2 in FIGURE 2. As can be seen from the waveforms depicted in FIGURES 5(b) and 5(d), the amplitude of the 1H and 2H SVM output signals are approximately the same. Thus, the SVM automatic gain control system maintains an optimal amplitude range for the scanning velocity modulation signal at multiple scan frequencies.

12
CLAIMS

1 1. A video display apparatus, operable at a plurality scanning frequencies
2 and including scanning beam velocity modulation, comprising:

3 a controllable scanning velocity modulation signal amplifier for
4 generating an scanning velocity modulation deflection signal responsive to a
5 scanning velocity modulation signal; and,

6 means for generating a control signal coupled to said amplifier for
7 open loop control of said scanning velocity modulation deflection signal in
8 amplitude responsive to selected ones of said plurality of scanning frequencies.

1 2. The video display apparatus of claim 1, wherein said control signal
2 reduces said scanning velocity modulation deflection signal amplitude in
3 accordance with an increasing scanning frequency of said plurality of scanning
4 frequencies.

1 3. The method according to claim 1, comprising a further step of:
2 selecting a different one of said plurality of horizontal scanning
3 frequencies and reducing said amplitude of a scanning velocity modulation signal
4 in accordance with said different one having a horizontal scanning frequency
5 greater than a horizontal scanning frequency of a prior selection.

1 4. A method for controlling scan velocity modulation in a video display
2 apparatus operable at a plurality of horizontal scanning frequencies, comprising
3 the steps of:
4 generating from a signal coupled for display by said apparatus a scanning
5 velocity modulation signal with a range of amplitudes representative of a
6 horizontal scanning frequency of said signal coupled for display;
7 determining said horizontal scanning frequency of said signal coupled for display;
8 generating a control signal in accordance with said determined scanning
9 frequency to maintain said scanning velocity modulation signal within said range
10 of amplitudes substantially independent of said horizontal scanning frequency of
11 said signal coupled for display.

1 5. The method according to claim 5, wherein said control signal generating
2 step comprises the step of;

3 representing said determined horizontal scanning frequency with a DC
4 voltage that varies proportionally as a function of said determined horizontal
5 scanning frequency.

1 6. The method according to claim 8, comprising the step of;

2 controlling said amplitude of said scanning velocity modulation
3 signal responsive to said DC voltage.

1 7. The method according to claim 5, wherein said control signal generating
2 step comprises the step of;

3 representing said determined horizontal scanning frequency with a digital
4 signal generated by a microprocessor.

1 8. The method according to claim 10 comprises the step of;

2 controlling said amplitude of said scanning velocity modulation
3 signal responsive to said digital signal.

1 9. A video display apparatus with scan velocity modulation and operable at a
2 plurality of scanning frequencies comprising:

3 means for generating a scan velocity modulation signal from a display
4 signal coupled to said apparatus, said scanning velocity modulation signal having
5 an amplitude range;

6 means for determining said horizontal scanning frequency of said display
7 signal;

8 means for generating a control signal responsive to said determined
9 horizontal scanning frequency; and,

10 a differential amplifier responsive to said control signal for selectively
11 controlling said scanning velocity modulation signal to maintain said scan
12 velocity modulation signal within said amplitude range substantially independent
13 of said determined horizontal scanning frequency.

14

1 10. The video display apparatus according to claim 12, wherein said means for
2 selectively controlling reduces said amplitude of said scanning velocity
3 modulation signal in accordance a frequency increase of said determined
4 horizontal scanning frequency.

1 11. The video display apparatus according to claim 12, wherein said means
2 for selectively controlling halves said amplitude of said scanning velocity
3 modulation signal for each octave increase in said determined horizontal
4 scanning frequency.

1 12. The video display apparatus according to claim 12, wherein said control
2 signal representing said determined horizontal scanning frequency is a DC
3 voltage that varies proportionally as a function of said determined horizontal
4 scanning frequency.

1 13. The video display apparatus according to claim 12, wherein said control
2 signal representing said determined horizontal scanning frequency is a digital
3 signal generated by a microprocessor.

1 14. The video display apparatus according to claim 16, wherein said digital
2 signal sets a gain register to control said amplitude of said scanning velocity
3 modulation signal.

1/4

FIG. 1







FIG. 2



2/4



3/4



4/4

FIG.5a




FIG.5b




FIG.5c





FIG.5d



EXPRESS EL 722193709 US

#3

Please type a plus sign (+) inside this box →



PTO/SB/01 (10-00)

Approved for use through 10/31/2002. OMB 0651-0032

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63)

☐ Declaration Submitted With Initial Filing **OR** ☒ Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)

Attorney Docket Number RCA 89383

First Named Inventor Jeffrey Owen Allender

COMPLETE IF KNOWN

Application Number 09/913,097

Filing Date August 9, 2001

Group Art Unit N/A

Examiner Name N/A

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

CONTROL OF SCANNING VELOCITY MODULATION AT MULTIPLE SCANNING FREQUENCIES

the specification of which (Title of the Invention)

☐ is attached hereto

OR

☒ was filed on (MM/DD/YYYY) 02/04/2000 as United States Application Number or PCT International

Application Number PCT/US00/02989 and was amended on (MM/DD/YYYY) (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims as amended specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56, including for continuation-in-part applications, material information which became available between the filing date of the prior application and the national or PCT international filing date of the continuation-in-part application.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY) Country	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)	<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.
60/119,278	02/09/1999	

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 21 minutes to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → +

PTO/SB/01 (10-00)

Approved for use through 10/31/2002. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

Direct all correspondence to: ☐ Customer Number or Bar Code Label OR ☐ Correspondence address below

Name	JOSEPH S. TRIPOLI		
Address	THOMSON MULTIMEDIA LICENSING INC.		
Address	P. O. BOX 5312		
City	State	ZIP	
PRINCETON	NJ	08543-5312	
Country	Telephone	Fax	
USA	(609) 734 - 9443	(609) 734 - 9700	

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

NAME OF SOLE OR FIRST INVENTOR:

☐ A petition has been filed for this unsigned inventor

Given Name

JEFFREY OWEN

Family Name or Surname

ALLENDER

Inventor's Signature

Jeffrey Owen Allender

Date

8/10/2001

Residence: City

Morristown

State

Indiana

Country

U.S.A.

Citizenship

U.S.A.

IN

Mailing Address 860E 1000 North

Mailing Address

City

Morristown

State

Indiana

ZIP

46161

Country

U.S.A.

NAME OF SECOND INVENTOR:

☐ A petition has been filed for this unsigned inventor

Given Name

GENE KARL

Family Name or Surname

SENDELWECK

Inventor's Signature

Gene Karl Sendelweck

Date

August 10, 2001

Residence: City

Indianapolis

State

Indiana

Country

U.S.A.

Citizenship

U.S.A.

IN

Mailing Address 5415 East 72nd Street

Mailing Address

City

Indianapolis

State

Indiana

ZIP

46250

Country

U.S.A.

☐ Additional inventors are being named on the _____ supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants : Jeffrey Owen Allender and Gene Karl Sendeleweck
Serial No. : 09/913,097 Filed : August 9, 2001
Int'l Appln. No. : PCT/US00/02989 Filed : February 4, 2000
For : CONTROL OF SCANNING VELOCITY MODULATION AT
MULTIPLE SCANNING FREQUENCIES

ATTENTION: PCT RECEIVING OFFICE

RESPONSE TO NOTIFICATION OF MISSING REQUIREMENTS UNDER 35 U.S.C. 371

Hon. Commissioner of Patents
Box PCT
Washington, D.C. 20231

Sir:

In response to the NOTIFICATION OF MISSING REQUIREMENTS UNDER 35 U.S.C. 371, mailed October 23, 2001, and relating to the above-identified application Serial No. 09/913,097, Applicants hereby submit the following:


- 1) An executed Declaration (PTO/SB/01) – 2 pages.
- 2) An executed Assignment with Recordal Cover Page – 2 pages.
- 3) Copy of Notification of Missing Requirements (371 Formalities Letter, Confirmation No. 3467).
- 4) Petition for Extension of Time under 37 CFR 1.136(a).

Please charge the following fees to Deposit Account No. 07-0832:

- 1) A surcharge of **\$130.00** required under 37 CFR 1.497(a) and (b) for filing the Declaration on a date later than the appropriate 30 months from the priority date (37 CFR 1.492(e)).
- 2) An assignment recordation fee of **\$40.00**.
- 3) A petition fee of **\$110.00** for a one month extension.

Please charge any additional fees and credit any overpayments to Deposit Account No. 07-0832. A duplicate copy of this letter is enclosed for use in charging the deposit account.

Respectfully submitted,


Francis A. Davenport
Registration No. 36,316
609/734-9864

Encls.

THOMSON multimedia Licensing Inc.
PO Box 5312
Princeton, NJ 08543-5312

DATE: January 18, 2001

01/26/2002 UEDUVIJE 00000055 070632 09313097
01 FC:154 130.00 CH

CERTIFICATE OF MAILING UNDER 37 CFR 1.10

I hereby certify that this Response to Notification of Missing Requirements is being deposited with the United States Postal Service via "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated below and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231 on:

January 18, 2002
Date of Deposit

Anelia F. Urban
Anelia F. Urban, Paralegal
(Name of Person mailing papers)